



Small bandsaw line 60

SBL60 is designed for the flexible production company. It's a one-man operation with fast manual adjustment possibilities. Combined with a tilt able bandsaw this unit can resaw many different profiles.

The units are developed over centuries and are well known for reliability and simple maintenance. All spare parts are directly available from the System Hall HQ. SBL60 is a real space saver, It only uses a area of 21 x 13 meters this enables you to place it even in the smallest facilities.

Technical

Small Bandsaw Line 60

Pieces per minute: 4,2 m pieces at 14 p/m Length: 1,8 – 6 m Max width: Before moulder 70 mm. after moulder 45 mm Min width: 75 mm Max thickness: 100 mm Min thickness: 22 mm Packet size (Infeed): 1,2 x 1,2 m Packet size (Outfeed): 1,2 x 1,2 m Max weight: 4000 kg Color frame: RAL 1015 Color moving parts: RAL 2004





Sideview infeed

100: Buffer transport

One buffer slot for pack and one slot where the pack gets fed in to the line.


101: Pack tilt

Lifts the pack and tilts om one layer at the time.

102: Downfall and stick conveyor

Receives the sticks when each layer drops from the pack tilt, transports the sticks outside the line.

103: Receiving conveyor Receives the layers from the pack tilt, also equipped with lifting table and hooks to send the pieces one by one to the infeeder.



Sideview outfeed

201: Elevator


Lifts the material directly when leaving the bandsaw.

202: Side conveyor Transports the resawed pieces to the automatic stacker.


203: Automatic stacker

Fully automatic stacking unit with even end adjuster that keeps the packs even.

204: Buffer transport



Overview line-setup





www.systemhall.com sales@systemhall.com Phone: +46(0)346-577 30